

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**




FIG. 1
(Prior Art)




FIG. 2
(Prior Art)




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 9A





FIG. 9B

FIG. 9C



Serial No. 10/033,364 Docket No. 856063.678
Inventor(s): Giuseppe Di Gregorio et al.
Express Mail No. EV449556775US "REPLACEMENT SHEET"

Parameters	
x = 0.88	y = 0.23
mag = 0.91	phase = -14.38
imped = 134.62 - j 344.87	admit = 0.00 + j 0.00
freq = 1.98 GHz	Gamma = 0.88 - j 0.23
VSWR = 20.68	RL = 0.84 dB

OPEN




FIG. 10

Parameters	
x = -0.99	y = 0.06
mag = 0.99	phase = 176.79
imped = 0.20 - j 1.40	admit = 0.10 - j 0.70
freq = 2.05 GHz	Gamma = -0.99 + j 0.06
VSWR = 254.24	RL = 0.07 dB

SHORT




FIG. 11



Serial No. 10/033,364 Docket No. 856063.678
Inventor(s): Giuseppe Di Gregorio et al.
Express Mail No. EV449556775US "REPLACEMENT SHEET"

Parameters	
x = -0.01	y = -0.02
mag = 0.02	phase = -123.80
imped = 48.71 - j 1.85	admit = 0.02 + j 0.00
freq = 2.04 GHz	Gamma = -0.01 - j 0.02
VSWR = 1.05	RL = 32.81 dB

L1




FIG. 12

Parameters	
x = 0.00	y = -0.01
mag = 0.01	phase = -83.34
imped = 50.12 - j 1.14	admit = 0.02 + j 0.00
freq = 2.05 GHz	Gamma = -0.00 - j 0.01
VSWR = 1.02	RL = 38.83 dB

L2




FIG. 13

Office
MAY 21 2004
PATENT & TRADEMARK OFFICE

Serial No. 10/033,364 Docket No. 856063.678
Inventor(s): Giuseppe Di Gregorio et al.
Express Mail No. EV449556775US "REPLACEMENT SHEET"

Parameters	
x = 0.29	y = -0.09
mag = 0.31	phase = -16.62
imped = 89.26 - j 17.20	admit = 0.01 + j 0.00
freq = 1.94 GHz	Gamma = 0.29 - j 0.09
VSWR = 1.88	RL = 10.30 dB

L3




FIG. 14

Parameters	
x = 0.29	y = -0.06
mag = 0.30	phase = -11.91
imped = 90.05 - j 12.14	admit = 0.01 + j 0.00
freq = 1.90 GHz	Gamma = 0.29 - j 0.06
VSWR = 1.85	RL = 10.52 dB

L4





FIG. 15



Parameters	
x = -0.22	y = -0.89
mag = 0.91	phase = -104.09
imped = 3.67 - j 38.87	admit = 0.00 + j 0.03
freq = 2.00 GHz	Gamma = -0.22 - j 0.89
VSWR = 21.90	RL = 0.79 dB

C






FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29